



**VURA®**  
Time To Build Better

# VURA DenStone 200<sup>TM</sup>

**VURA DenStone 200** is a Nano lithium chemistry based densifier and marble hardener that penetrates into the marble and reacts with the marble to form compounds which expand and fill the pores in the stone. Not only reduce the porosity but also leads to enhanced shine and longevity of polish.

Densification makes the marble harder and denser. It is colorless liquid increase the stone strength and provides high gloss finish. It is lithium chemistry for marble, natural stones, terrazzo and concrete.

## CHARACTERISTICS

- Easy application
- Strengthen the surface
- Penetrates and seals new and existing marble, natural stones, terrazzo and concrete
- Improves chemical and water resistance
- Prolongs finish of polished surfaces
- Resists stains and Increase abrasion
- Making surface easy to use and maintain
- Environmentally friendly, water based formula
- Interior and Exterior use
- Protects against efflorescence
- Enhance gloss after polish
- Preserves Natural look

## USAGE

For the treatment of ground and polished absorbent marble, natural stone, slate, limestone, sandstone, granite, travertine etc.

## INSTRUCTIONS FOR USE

### **SURFACE PREPARATION:**

- Clean the surface to remove any dirt, laitance, curing compound and surface coating
- Surface should be sound, clean and free of waxes, dirt and coatings

### **APPLICATION:**

- To prepare the surface for application first grind the stone with the abrasives
- Wash the floor with Floor cleaner & make sure it's completely dry before starting application
- Cover adjoining fabric, plastic or parquet floors. Protect furniture from splashes
- Pour onto the surface and spread it evenly for ease of absorption
- Wait for each coat to be completely absorbed before applying the next coat
- For maximum effect do 5 to 6 applications. Stop applying when the stone no longer absorbs
- Wait at minimum of 24 hours after the last coat and then use the abrasives
- Apply 2-3 additional coats for best results
- Finish the polishing process

### **Vura Bau-Chemie LLP**

1302, 13<sup>th</sup> Floor,  
Elite Business Hub, Sola,  
Ahmedabad 380060,  
Gujarat, India.

[www.vura.ae](http://www.vura.ae)

+91 79 4849 2890  
[care@vura.ae](mailto:care@vura.ae)





**VURA®**  
Time To Build Better

## PRECAUTIONS

- Do not dilute
- Close the container lid properly after use
- Avoid application during, before & after heavy rain
- Before taking up application on a large area, it is advisable to check the performance of the product on a relatively small area

## COVERAGE

Application after 200 grit, approx. 200-250 sq. ft. / litre, depending on the porosity of the stone.

## TECHNICAL DATA

Color	:	Slightly cloudy
Density	:	1.02 g/ml
Ph	:	10.5-11.0
VOC Content	:	<50g/ml
Flash Point	:	Not applicable
Freeze Point	:	0°C

## PACK SIZE

1 L / 5 L / 20 L

## SHELF LIFE

Shelf life is 12 months from the date of manufacturing in unopened condition.  
Store in a cool & dry place.

## HEALTH & SAFETY:

- Use rubber hand gloves & safety goggles, while using
- In case of contact with skin, wash with plenty of water
- Keep out of reach of children's
- Do not smoke during application
- Please read Material Safety Data Sheet before handling or using the products

### IMPORTANT NOTICE:

The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.

This Datasheet is an information document drawn up in good faith. The information herein is based on tests carried out in our labs and is correct on the basis of our experience, but must be considered only as indicative because of the nature of the product whose behaviour varies with the minimal change in the surrounding conditions (environmental parameters, materials it comes into contact with, storage and ageing methods, etc.) For this reason, the information herein, even if based on our best knowledge, is no guarantee for the user since the customer's application, use and processing of our products and of the final product are beyond our control and are therefore wholly the customer's responsibility. We trust the tests we carried out can be a useful indication, even if we cannot accept any responsibility with regard to the result of your processing. It is the user's responsibility and duty to perform preliminary tests on the specific application, to assess suitability to the required use as it is his/her duty to check that the use of our products complies with the current laws, regulations, provisions and patents. This information must not be considered as an authorization and is no encouragement to infringe any patent. The data can be changed without notice and must not be considered as legally meaningful.

This technical data sheet supersedes all previous editions relevant to this product. Please be aware that this Technical Data Sheet only relates to a product manufactured in the specific relevant production site.

### Vura Bau-Chemie LLP

1302, 13<sup>th</sup> Floor,  
Elite Business Hub, Sola,  
Ahmedabad 380060,  
Gujarat, India.

[www.vura.ae](http://www.vura.ae)

+91 79 4849 2890  
[care@vura.ae](mailto:care@vura.ae)

