



**VURA®**  
Time To Build Better

# VURA PowerSeal+™

## TRANSPARENT SURFACE PROTECTION AGENT, EXCELLENT WATER & OIL REPELLENT AND STAIN RESISTANT TO THE TREATED SURFACE

**VURA PowerSeal +** water based synthetic polymer, provides a transparent and durable surface treatment for various kind of building materials such as Polished Porcelain Tiles, Natural stones, Marble and Granite, Terracotta, concrete and bricks. It provides excellent water and oil repellency to the treated surfaces, as well as stain resistance against oil, coffee, Ketchup and mustard among the others.

**VURA PowerSeal +** does not create a film on the surface and does not affect the original color and breathability of the material. The surfaces treated with Vura PowerSeal are easy to clean without altering original appearance of the stone.

### CHARACTERISTICS

- Water and oil-repellent with natural finish
- Excellent anti stain properties
- Easy to clean properties
- Long lasting treatment
- Water based
- Extreme Eco compatible
- The best environmentally-friendly stain protection for porcelain tiles, natural stone, marble and granite with polished, brushed and matt smoothed finishes
- Reduces absorption without affecting the material's natural look
- It protects and facilitates cleaning
- It is also ideal for grouting joints, ceramic and crackle effect surfaces, grit, resin- marble, and stone slabs
- Is also suitable for treating coloured cement tiles and manufactured stones
- It provides an anti-graffiti protection that prevents graffiti paint from bonding to surfaces

### ADVANTAGES

- Solvent free: Water based eco-friendly treatment
- Being a water-based product, it withstands residual humidity conditions and can therefore be applied 24-48 hours after the initial wash, thus speeding up the treatment
- Single-coat application: apply the product and rub it gently over the surface until it is completely absorbed
- Does not form surface film and does not yellow
- Ideal for protecting tables, as well as kitchen and bathroom tops
- The surface can be walked on after just 2 hours. (23° C & 50% R.H.)
- A product with an extremely low VOC and a low environmental impact

### APPLICATIONS

- **VURA PowerSeal +** is ready to use product so no dilution is required
- Apply **VURA PowerSeal +** evenly and continuously on a clean and dry surface using brush or fleece pad
- Remove any excess wet product before it dries (5-10 minutes in normal conditions) using a clean cloth
- **VURA PowerSeal +** can be applied with low pressure deck sprayer. Saturated brush, roller or by mop application in one or two layers depending on the surface porosity
- On highly absorbent materials, apply 2 coats of product with 20-30 min interval time
- The surface can be walked on after just 2 hrs.
- Water and oil repellent protection takes effect after 24 hrs.

#### Vura Bau-Chemie LLP

1302, 13<sup>th</sup> Floor,  
Elite Business Hub, Sola,  
Ahmedabad 380060,  
Gujarat, India.

[www.vura.ae](http://www.vura.ae)

+91 79 4849 2890  
[care@vura.ae](mailto:care@vura.ae)





**VURA®**  
Time To Build Better

## PLEASE NOTE

- Before applying to the entire surface, test the product on a small area to check for colour changes and evaluate the aesthetic result
- Do not apply the product externally if rain is forecast
- Do not protect against acidic aggression
- Outdoor flooring must be properly laid before being treated and must satisfy all the specific requirements, including: adequate sloping, properly executed expansion joints, perfect isolation from the underlying ground, proven compatibility with sub-zero temperatures
- Ventilate the premises well during use and while the product is drying
- This product must be applied to surfaces with temperature between 10° C and 30° C
- The treatment may be repeated after a certain period of time to maintain its effect, depending upon the type of material, the traffic load and wear level of the surface

## TECHNICAL DATA

1. Appearance	: Liquid
2. Color	: Clear
3. Pack Size	: 1 L / 5 L
4. Ph	: 6.0-8.0
5. Density (g/ml)	: 1.0 + 0.1
6. Storage Temperature	: 5° C to 30° C
7. Working Temperature	: 10° C to 30° C
6. Coverage	: <b>Approximate coverage</b>
(Coverage shown for guidance	Polished Porcelain Tiles : 30-50 m <sup>2</sup>
Purposes only and for single coat)	Polished Marble / Granite : 20-30 m <sup>2</sup>

## SHELF LIFE

12 months (Store in cool, dry condition in well-sealed containers and well-ventilated place. Don't store under direct sunlight.)

## OTHER INFORMATION

Should you need support or advice, please consult our advisory service for architects and craftsman on the contact information you will find on the local **VURA** website.

### IMPORTANT NOTICE:

The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.

This Datasheet is an information document drawn up in good faith. The information herein is based on tests carried out in our labs and is correct on the basis of our experience, but must be considered only as indicative because of the nature of the product whose behaviour varies with the minimal change in the surrounding conditions (environmental parameters, materials it comes into contact with, storage and ageing methods, etc.) For this reason, the information herein, even if based on our best knowledge, is no guarantee for the user since the customer's application, use and processing of our products and of the final product are beyond our control and are therefore wholly the customer's responsibility. We trust the tests we carried out can be a useful indication, even if we cannot accept any responsibility with regard to the result of your processing. It is the user's responsibility and duty to perform preliminary tests on the specific application, to assess suitability to the required use as it is his/her duty to check that the use of our products complies with the current laws, regulations, provisions and patents. This information must not be considered as an authorization and is no encouragement to infringe any patent. The data can be changed without notice and must not be considered as legally meaningful.

This technical data sheet supersedes all previous editions relevant to this product. Please be aware that this Technical Data Sheet only relates to a product manufactured in the specific relevant production site.

### Vura Bau-Chemie LLP

1302, 13<sup>th</sup> Floor,  
Elite Business Hub, Sola,  
Ahmedabad 380060,  
Gujarat, India.

[www.vura.ae](http://www.vura.ae)

+91 79 4849 2890  
[care@vura.ae](mailto:care@vura.ae)

