



**VURA**<sup>®</sup>  
Time To Build Better

# VURA AquaRepWR<sup>™</sup>

**VURA AquaRep WR** is a ready-to-use water-based water repellent for natural stones. It is a high quality and economical water repellence system for mineral and alkaline substrates. It does not change the appearance of the substrate & gives a long lasting protection.

## CHARACTERISTICS

- Easy to use – Brushable / Sprayable
- UV resistance
- Durable
- Water repellent
- Retains breathability of substrate (does not trap moisture)
- Resistance to alkalis
- Tack-free drying
- Invisible coating, does not change the color
- Cost effective

### **WATER REPELLENT TREATMENT FOR:**

- Limestone & sandstones
- Clay, concrete & mortar
- Mangalore tiles
- Natural and artificial porous stones
- Bricks

### **PREPARATION OF A SAMPLE AREA:**

Surface temperature should be between 10°C to 35°C and surface should be clean and free of dirt, waxes, and protective coatings. Ensure that the area is well ventilated, and the surface is dry. Before starting we recommend preparing a sample area of 1-2m<sup>2</sup> to examine the efficiency of the impregnation.

## INSTRUCTIONS FOR USE

### **SURFACE PREPARATION:**

- Surface should be dry and free from all debris, dirt, oil, grease, wax and all other contamination which could prevent penetration
- Clean the saturated dirt of surface by thorough wire brushing, cleaning with compressed air followed by water washing
- Degrease oil & grease by using appropriate solvents
- Allow the surface to dry completely before the application
- Protect adjacent areas that are not to be treated. Since this is an impregnating product
- Seal the cracks using appropriate suitable products

### **APPLICATION:**

- Apply one liberal coat of **VURA AquaRep WR** by brushing / spraying evenly on the prepared surface
- Apply second coat wet on wet, to improve the penetration rate & performance
- Allow it to dry for 24 hrs.
- After usage, close the tins well sealed

### **Vura Bau-Chemie LLP**

1302, 13<sup>th</sup> Floor,  
Elite Business Hub, Sola,  
Ahmedabad 380060,  
Gujarat, India.

[www.vura.ae](http://www.vura.ae)

+91 79 4849 2890  
[care@vura.ae](mailto:care@vura.ae)





**VURA**<sup>®</sup>  
Time To Build Better

## **PRECAUTIONS**

- Do not dilute
- Close the container lid properly after use
- VURA AquaRep WR does not protect stones from strong acid
- Avoid application during, before & after heavy rain
- Before applying over the natural stones like sandstone, slate or Dholpur, sampling should be done on a small area to check its suitability
- Before taking up application on a large area, it is advisable to check the performance of the product on a relatively small area

## **TECHNICAL DATA**

Form	:	Liquid
Color	:	Clear Transparent
Density	:	1.02 g/ml
Surface Dry Time	:	3-4 hrs
pH	:	10-12
Application	:	By Brush or Spray
Water Repellency	:	Bead form

## **COVERAGE**

70 to 200 Sq. ft. / litre (depending on the porosity of stone)

## **PACK SIZE**

20 L

## **SHELF LIFE**

Shelf life is 12 months from the date of manufacturing in unopened condition.  
Store in a cool & dry place.

## **HEALTH & SAFETY:**

- Use rubber hand gloves & safety goggles, while using
- In case of contact with skin, wash with plenty of water
- Keep out of reach of children's
- Do not smoke during application
- Please read Material Safety Data Sheet before handling or using the products

### **IMPORTANT NOTICE:**

The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.

This Datasheet is an information document drawn up in good faith. The information herein is based on tests carried out in our labs and is correct on the basis of our experience, but must be considered only as indicative because of the nature of the product whose behaviour varies with the minimal change in the surrounding conditions (environmental parameters, materials it comes into contact with, storage and ageing methods, etc.) For this reason, the information herein, even if based on our best knowledge, is no guarantee for the user since the customer's application, use and processing of our products and of the final product are beyond our control and are therefore wholly the customer's responsibility. We trust the tests we carried out can be a useful indication, even if we cannot accept any responsibility with regard to the result of your processing. It is the user's responsibility and duty to perform preliminary tests on the specific application, to assess suitability to the required use as it is his/her duty to check that the use of our products complies with the current laws, regulations, provisions and patents. This information must not be considered as an authorization and is no encouragement to infringe any patent. The data can be changed without notice and must not be considered as legally meaningful.

This technical data sheet supersedes all previous editions relevant to this product. Please be aware that this Technical Data Sheet only relates to a product manufactured in the specific relevant production site.

### **Vura Bau-Chemie LLP**

1302, 13<sup>th</sup> Floor,  
Elite Business Hub, Sola,  
Ahmedabad 380060,  
Gujarat, India.

[www.vura.ae](http://www.vura.ae)

+91 79 4849 2890  
[care@vura.ae](mailto:care@vura.ae)

