



VURA[®]
Time To Build Better

VURA **FiSeal Pro**[™]

VURA FiSeal Pro is a ready to use nano impregnating sealer providing advance protection against water, oil and other stains. The product is absorbed by the capillary forces of the stone and can therefore penetrate into the stone structure.

CHARACTERISTICS

- Fluoropolymer based product
- Nano impregnating technology
- Breathable
- Resistance to UV radiation
- The color of the stone is normally not enhanced (preliminary test)
- Enhance adhesion strength
- Reduction of water and dirt absorption during periods of moisture
- Maintenance of breathing properties because there is no surface layer

USAGE

Back and 4 sides of natural stone surfaces such as marble, granite, travertine, sandstone, limestone and absorbent material.

INSTRUCTIONS FOR USE

CLEANING:

- Surface must be clean, dry and free from all waxes, layers/coatings
- It shall be taken into consideration that the stone contains no harmful salts (nitrates, sulphates, chlorides)
- The surface temperature should be between 10° to 35° C and sound
- Rinse well with water without fail after cleaning
- Before the stone is given its protective treatment, it must be totally dry. As a rule, this is the case after 1-2 days at the earliest
- Ensure that the area is well ventilated, and the surface is dry

PRE-TEST:

- Before starting the treatment, we recommend executing pre-tests, to examine the efficiency of the treatment, to evaluate the appearance of the treated surfaces (color enhancement) and to ascertain the material consumption as exactly as possible

PROCEDURE OF THE TREATMENT:

- The best conditions for a treatment are an object- and surrounding temperature of 15° - 25°C and a protection from direct solar radiation and humidity exposure until the effectiveness of the protective effect
- In general, a single application is sufficient
- Apply the product with a brush, mop or an airless spraying equipment at low pressure (max. 1 bar over pressure) and a jet distance of 5-10 cm (condition: tubes and seals must be resistant to solvents)
- Approx. 20 minutes after application, respectively before the product has dried on the surface, any excess which has not been absorbed by the polished surface has to be completely removed with a suitable cloth so that no residue should remain on the polished surface

Vura Bau-Chemie LLP

1302, 13th Floor,
Elite Business Hub, Sola,
Ahmedabad 380060,
Gujarat, India.

www.vura.ae

+91 79 4849 2890
care@vura.ae





VURA[®]
Time To Build Better

SAFETY TIPS

- Keep out of reach of Children
- Do not disperse into the environment after use
- For safety related information, please refer to the Material Safety Data Sheet available on the **VURA** website

TECHNICAL DATA

- | | | |
|----------------------------|---|------------------------------------|
| 1. Appearance | : | Clear Transparent |
| 2. Form | : | Liquid |
| 3. Pack Size | : | 1L / 5L |
| 4. Density | : | 0.8 g/ml |
| 5. Application Temperature | : | 5° to 35° C |
| 6. Full Cure Time | : | 24-72 hours at +23° C and 50% R.H. |

CONSUMPTION

150-250 sq. ft./ltr (depends on the porosity of stone)

SHELF LIFE

12 Months if stored in cool place & tightly closed original container.

HEALTH & SAFETY

Read safety data sheet before handling or using this product.

IMPORTANT NOTICE:

The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.

This Datasheet is an information document drawn up in good faith. The information herein is based on tests carried out in our labs and is correct on the basis of our experience, but must be considered only as indicative because of the nature of the product whose behaviour varies with the minimal change in the surrounding conditions (environmental parameters, materials it comes into contact with, storage and ageing methods, etc.) For this reason, the information herein, even if based on our best knowledge, is no guarantee for the user since the customer's application, use and processing of our products and of the final product are beyond our control and are therefore wholly the customer's responsibility. We trust the tests we carried out can be a useful indication, even if we cannot accept any responsibility with regard to the result of your processing. It is the user's responsibility and duty to perform preliminary tests on the specific application, to assess suitability to the required use as it is his/her duty to check that the use of our products complies with the current laws, regulations, provisions and patents. This information must not be considered as an authorization and is no encouragement to infringe any patent. The data can be changed without notice and must not be considered as legally meaningful.

This technical data sheet supersedes all previous editions relevant to this product. Please be aware that this Technical Data Sheet only relates to a product manufactured in the specific relevant production site.

Vura Bau-Chemie LLP

1302, 13th Floor,
Elite Business Hub, Sola,
Ahmedabad 380060,
Gujarat, India.

www.vura.ae

+91 79 4849 2890
care@vura.ae

