



**VURA**<sup>®</sup>  
Time To Build Better

# VURA<sup>®</sup> PreVento<sup>™</sup>

**VURA PreVento** is a solvent based impregnator for façade, used for natural porous stones and preserves a natural look. It is hydrophobic and oleophobic stone impregnator. It is an economical nano impregnating sealer designed for protection of porous stones against water, oil and other stains.

## CHARACTERISTICS

- Nano Impregnating technology
- Hydrophobic and oleophobic based product
- Designed for protection of porous stones
- Preserves natural look
- Weather resistant

## USAGE

- Natural stones such as marble
- Sandstones
- Granite
- Travertine
- Limestone

## INSTRUCTIONS FOR USE

### **SURFACE PREPARATION / CLEANING:**

- Surface preparation should be between 10 to 35 deg C and structurally sound, clean and free from waxes, dirt and coatings
- The surface should be dry
- Ensure that area is well ventilated

### **APPLICATION:**

- Spread the material over the substrate using a mop / paint brush / roller or cloth
- Use garden sprayer pump. Do not use power sprayer
- Allow **Vura PreVento** to penetrate into the surface for 15-30 minutes. During this time, spread the **Vura PreVento** over entire area to ensure even penetration
- Do not allow excess material to dry on surface
- Second coat can be applied after 30-40 minutes after initial application, if needed for porous absorbent surface
- To remove excess Vura PreVento, after 15-30 minutes of application, Wipe the entire area with clean dry towel
- To remove residue, reapply a thin coat of Vura PreVento, allow to dwell it for 2-3 minutes, agitate with dry nylon pad and dry thoroughly with clean, dry towel
- Full cured is achieved after 24-72 hrs
- Foot traffic is allowed after 6-8 hrs

## CLEANING

- Clean the tools with mineral spirit immediately after application
- Allow them to dry in a well-ventilated area

### **Vura Bau-Chemie LLP**

1302, 13<sup>th</sup> Floor,  
Elite Business Hub, Sola,  
Ahmedabad 380060,  
Gujarat, India.

[www.vura.ae](http://www.vura.ae)

+91 79 4849 2890  
[care@vura.ae](mailto:care@vura.ae)





**VURA®**  
Time To Build Better

## COVERAGE

Apprx. 150 -250 m2/Litre (depends on porosity of stone)

## PRECAUTIONS

- Keep out of the reach of the Children
- Do not inhale
- Avoid prolong exposure to product. Use in a well-ventilated area.
- May cause skin, eye and respiratory irritation
- Do not freeze or store above 40°C
- Do not mix with other Chemicals
- Ingestion – do not induce vomiting. Call a physician
- Eye contact – flush thoroughly with water for at least 15 minutes. Remove contact lenses. Call a physician if eye irritation persists
- Skin contact – wash skin with mild soap and water. Call a physician, if skin irritation persists.
- Wash clothes before wearing again
- Inhalation – remove to fresh air. Call a physician if respiratory irritation persists

## TECHNICAL DATA

- |                  |               |
|------------------|---------------|
| 1. Form          | : Liquid      |
| 2. Color         | : Transparent |
| 3. Density       | : 0.8 g/ml    |
| 4. Expected wear | : 3-5 yrs     |
| 5. Pack Size     | : 1 L         |

## SHELF LIFE

12 months if stored in a cool place & tightly closed original container.

## HEALTH & SAFETY

Read safety data sheet before handling or using this product.

### IMPORTANT NOTICE:

The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.

This Datasheet is an information document drawn up in good faith. The information herein is based on tests carried out in our labs and is correct on the basis of our experience, but must be considered only as indicative because of the nature of the product whose behaviour varies with the minimal change in the surrounding conditions (environmental parameters, materials it comes into contact with, storage and ageing methods, etc.) For this reason, the information herein, even if based on our best knowledge, is no guarantee for the user since the customer's application, use and processing of our products and of the final product are beyond our control and are therefore wholly the customer's responsibility. We trust the tests we carried out can be a useful indication, even if we cannot accept any responsibility with regard to the result of your processing. It is the user's responsibility and duty to perform preliminary tests on the specific application, to assess suitability to the required use as it is his/her duty to check that the use of our products complies with the current laws, regulations, provisions and patents. This information must not be considered as an authorization and is no encouragement to infringe any patent. The data can be changed without notice and must not be considered as legally meaningful.

This technical data sheet supersedes all previous editions relevant to this product. Please be aware that this Technical Data Sheet only relates to a product manufactured in the specific relevant production site.

### Vura Bau-Chemie LLP

1302, 13<sup>th</sup> Floor,  
Elite Business Hub, Sola,  
Ahmedabad 380060,  
Gujarat, India.

[www.vura.ae](http://www.vura.ae)

+91 79 4849 2890  
[care@vura.ae](mailto:care@vura.ae)

