



**VURA<sup>®</sup>**

Time To Build Better

# STONE CARE

PRODUCT CATALOGUE



**LEADER,**  
WHO CAN SEE TOMORROW,  
**BUILD  
TOMORROW!**

# A FUTURISTIC BRAND CONCEIVED AND NURTURED WITH THE EXPERIENCE OF 120 YEARS


Vura Bau-Chemie LLP is a global brand that manufactures adhesives, sealants, repairs, waterproofing, maintenance & building products which are **formulated with world-class German polymers & technology**. It has developed a comprehensive product range based on international standards to facilitate global construction chemical and building materials market. The brains behind the product development have a combined experience of more than 120 years in the same industry. With this abundance of experience, the company is ready to build better!





THE MOST INNOVATIVE,  
CUSTOMER-CENTRIC,  
INCLUSIVE & SUSTAINABLE  
**BUILDING**  
CHEMISTRY COMPANY







**PRE PROTECTION SYSTEM**



PRE PROTECTION  
**FiSeal Pro**<sup>®</sup>  
VURA

## SOLVENT BASED FIVE SIDE IMPREGNATING SEALER

**Vura FiSeal Pro** is a ready to use nano impregnating sealer providing advance protection against water, oil and other stains. The product is absorbed by the capillary forces of the stone and can therefore penetrate into the stone structure.

### CHARACTERISTICS

- Fluoropolymer based product
- Nano impregnating technology
- Breathable
- Resistance to UV radiation
- The color of the stone is normally not enhanced (preliminary test)
- Enhance adhesion strength
- Reduction of water and dirt absorption during periods of moisture
- Maintenance of breathing properties because there is no surface layer

### WHERE TO USE

Back and 4 sides of natural stone surfaces such as marble, granite, travertine, sandstone, limestone and absorbent material.



<b>Color</b>	: Clear Transparent
<b>Form</b>	: Liquid
<b>Density</b>	: 0.86 g/ml
<b>Application Temperature</b>	: 5 to 35°C
<b>Cure Time</b>	: 24-72 hours at +23°C and 50% R.H.
<b>Consumption</b>	: 150-250 sq. ft./ltr (depends on the porosity of stone)
<b>Packaging</b>	: 1 Ltr & 5 Ltr



PRE PROTECTION<sup>®</sup>  
**FiSeal+**  
VURA



## WATER BASE BACK COAT PENETRATING SEALER TO RESIST STAINS

**Vura FiSeal +** is chemically reactive penetrating sealer that creates cross linked internal membrane that fuses within the substrate to prevent contaminants from rising up to the surface without altering the adhesion properties of the adhesive. It allows moisture vapour transmission and does not adversely affect bonding of stone to substrate. Protects the material and improves its cohesion thanks to its consolidating action. It is a penetrating sealer to provide protection from water and stain absorption for most natural stones i.e. Marble, slate, granite, limestone, sand stone, travertine etc.

### CHARACTERISTICS

- Water-repellent and consolidating action
- Does not alter the material's appearance
- A VOC-free product with a low environmental impact
- UV resistant
- Breathable
- Blocks contaminants from rising to the material surface
- Easy to use
- Protection against moisture, water and most stains
- Does not substantially alter the adhesion characteristics of the adhesive
- For interior and exterior applications

### WHERE TO USE

Back and 4 sides of Natural stone surfaces such as Granite, Marble, Limestone, Slate, Travertine, Terracotta and Absorbent Material



<b>Color</b>	: Clear
<b>Application Temperature</b>	: From +5°C to +40 °C
<b>Cure Time</b>	: 12 hours at +23°C and 50% R.H.
<b>Consumption</b>	: Approx. 50-150 g/m <sup>2</sup> Consumption is depending on the density, porosity, texture, weather Conditions, application method and number of coats.
<b>Packaging</b>	: 5 Ltr



## JOINTING/BONDING SYSTEM





POLYESTER TECHNOLOGY<sup>®</sup>  
**PoliMast**  
VURA

**VURA PoliMast** is a high viscous thixotropic paste product based on unsaturated polyester resins containing filling agents suitable to glue and to fix marbles, onyx and stone in vertical surfaces. The hard product is well dry, polishable and sandable in a very short time. The product has low shrinkage, good adhesion in many stones. Low styrene content.

#### CHARACTERISTICS

- Good working properties creamy-soft consistency, especially on vertical surfaces
- Fast hardening (20-30 minutes)
- Good working properties (grinding, milling, drilling)
- Good polishing properties
- Very good adhesion on natural stones also at higher temperatures
- Resistance to water, petrol and mineral oils.

#### FIELD OF APPLICATION

**VURA PoliMast** is mainly used in stone processing industry for filling and bonding natural and artificial stones. Due to its creamy-soft consistency the product is suitable to fill larger areas especially on vertical surfaces



<b>Color</b>	: White
<b>Density</b>	: ~1.5 g/cm <sup>3</sup>
<b>Mixing ratio (by part)</b>	: 100 part VURA PoliMast 2-3 part Hardener
<b>Pot Life</b>	: 3-5 minutes
<b>Drying time</b>	: Surface dry : 4-5 minutes Hard dry : 20-30 minutes
<b>Packaging</b>	: 1.35 kg VURA PoliMast with 35 g tube



POLYESTER TECHNOLOGY<sup>®</sup>  
**PoliMast G**  
 VURA

**VURA PoliMast G** is a Transparent Gel product based on unsaturated polyester resins, suitable to glue and fix marbles, onyx and stone in vertical surfaces. The hard product is well dry, polishable and sandable in a very short time. The product has low shrinkage, good adhesion in many stones. Low styrene content.

#### CHARACTERISTICS

- Good working properties, knife-cut consistency
- Fast hardening (15-25 minutes)
- Good working properties
- Very good adhesion on natural stones also at higher temperatures
- Resistance to water, petrol and mineral oils.

#### FIELD OF APPLICATION

**VURA PoliMast G** is mainly used in stone processing industry for filling and bonding natural and artificial stones. Due to its creamy-soft consistency the product is suitable to fill larger areas especially on vertical surfaces



<b>Color</b>	: Yellow
<b>Appearance</b>	: Transparent Gel
<b>Density</b>	: ~1.12 g/cm <sup>3</sup>
<b>Mixing ratio (by part)</b>	: 2 to 3g of Hardener B in 100g of PoliMast G
<b>Pot Life</b>	: 3-5 minutes
<b>Drying time</b>	: Surface dry : 3-5 minutes Hard dry : 15-25 minutes
<b>Tensile strength</b>	: 50-60 N/mm <sup>2</sup>
<b>Bending strength</b>	: 90-100 N/mm <sup>2</sup>
<b>Packaging</b>	: 1 kg VURA PoliMast G with 35 g tube



POLYESTER TECHNOLOGY  
**PoliFillG**<sup>®</sup>  
VURA

**VURA PoliFill-G** is a gel-like semi solid 2 component product based on unsaturated premium polyester resins. It is thixotropic transparent gel with high viscosity for glueing and fixing marbles, stones, tiles and to fill cracks.

#### CHARACTERISTICS

- Premium polyester base thixotropic transparent gel
- Fast setting and curing time
- Easily to apply and polish
- Good UV Stability
- Very good adhesion on natural stone
- Bigger defects, corners and edges can be filled due to slow hardening and low tensions
- Resistant to water, petrol and mineral oils
- Grindable after hardening
- Colors can be mixed as per desired

#### APPLICATION AREAS

Granite, Marbles, Tiles, Sandstones, Cementitious tiles. Mainly used in the stone processing industry for filling and bonding light or white, transparent- crystalline natural stone such as Thassos, Carrara, Onyx etc. By adding little quantities of polyester coloring pastes to **VURA PoliFill-G** required color can be made. Thus, an appearance very similar to the stone or bonding joints which are almost invisible can be achieved. When working with crystalline natural stone we recommend mixing some crushed granular material in the filler to imitate the crystal structure of the stone.

Walls, floors, showers, damp areas, tile on tile applications, dry areas, and worktops.



**Color**

: Clear Translucent Gel

**Mixing ratio (by weight)**

: 1 to 2g of Hardener B (liquid) in 100g of PoliFill-G

**Gel time**

: 20-25 minutes

**Packaging**

: 1 kg with 20 ml hardener dropper bottle.



EPOXY TECHNOLOGY  
**Oxi7010**  
VURA

## 2 COMPONENTS, GEL FORM, EPOXY BASE THIXOTROPIC GLUE/PASTE

**Vura Oxi 7010** is two components, epoxy base, gel form, solvent-free, thixotropic paste to fill and to firmly glue marble, stone, granite, quartz and ceramic. Suitable for outdoor and indoor application with low yellowing. It is soft and light with high gloss and brightness.

### CHARACTERISTICS

- Very neutral colour & easy to spread
- Low VOC content
- Very low tendency to yellow
- High creeping strength due to gel like consistency
- Easy dosing and mixing by use
- Weather resistant bonding
- Good dimensional stability of the bonding layer
- Low tendency to fatigue
- Good adhesion on slightly humid stones
- Very low shrinkage during the hardening process and therefore low tensions in the bonding layer
- Very good alkali-stability, thus the adhesive is very well suited to bond concrete
- Excellently suited for bonding gas-impermeable materials as it is a solvent free product



	Part A	Part B
<b>Color</b>	: Hazy	Translucent
<b>Mixing ratio (by weight)</b>	: 2	: 1
<b>Packaging</b>	: 2.25 kg Combo Pack (A+B)	
	Resin	Hardener
	1.500 kg	0.750 kg
<b>Pot life</b>	: 25 minutes @ 25 ± 2 deg C	



**FILLING SYSTEM**





POLYESTER TECHNOLOGY  
**PoliFill<sup>®</sup>**  
VURA

**VURA PoliFill-L** is a water clear liquid, low viscous 2 component product based on UV-stabilized, unsaturated premium polyester resins. It is used for gluing and filling clear white marbles like Carrara and similar stones, also for filling the travertines and similar stones. Very stable to sunlight. It has a very low shrinkage. At low temperature, it has good reactivity.

#### CHARACTERISTICS

- Premium polyester base transparent liquid
- Low viscosity, therefore very good penetration
- No color of its own, therefore suited for light and white, mainly transparent-crystalline natural stones
- Fast setting and curing time
- Easily to apply and polish
- Good UV stability
- Very good adhesion on natural stone
- Bigger defects, corners and edges can be filled due to slow hardening and low tensions
- Resistant to water, petrol and mineral oils
- Grindable after hardening
- Colors can be mixed as per desired

#### APPLICATION AREAS

**VURA PoliFill-L** is mainly used in stone processing industry for strengthening of larger areas of light or white, transparent- crystalline natural stones e.g. Thassos, Carrara, Onyx etc.. Due to its low viscosity, liquid and colourless-transparent appearance, bonding can be made which maintain the stereoscopic structure of the stone.

By adding little quantity of Polyester color paste a similar look like natural stone can be achieved.

Granite, Marbles, Tiles, Sandstones, Cementitious tiles.

Walls, floors, showers, Damp areas, Tile on tile applications, Dry areas, worktops.



**Color**

: Water clear transparent

**Mixing ratio (by part)**

: 100 : 1-2

**Gel time**

: 20-25 minutes

**Packaging**

: 1 Ltr with 20 ml hardener dropper bottle.



EPOXY TECHNOLOGY<sup>®</sup>  
**Oxi4010**  
 VURA

**VURA Oxi 4010** is a two-component, low viscous, transparent and non-yellowing epoxy resin system with a modified hardener. It is used for firmly closing cracks and pores of any type of Natural stones even for light color stones.

#### CHARACTERISTICS

- Hardens relatively quickly
- It has highly penetrative properties on account of its low viscosity
- Clear transparent, best suitable for light natural stones
- Solvent free epoxy system
- Weather-resistant, Chemical resistant
- Excellent grinding and polishing properties
- Increases the firmness and improves the quality of natural stone surfaces
- Increases the yield and the productivity
- Excellent product to fill pinholes and cracks of light-colored marble
- Good reactivity at low temperature, medium hardness

#### USAGE / APPLICATION AREA

- All type of marble/granite
- Natural Stones

**VURA Oxi 4010** is mainly used in the stone-working industry for strengthening porous and fissured natural stone slabs, concrete and concrete ashlar and improving their surface qualities. In combination with spun glass fabrics, it is also used for strengthening brittle natural stone slabs.



	Part A	Part B
<b>Color</b>	: Transparent	Transparent
<b>Mixing ratio (by weight)</b>	: 4	: 1
<b>Pot Life</b>	: 25-30 minutes (20°C)	
<b>Packaging</b>	: 1.25 Ltr Combo Pack (A+B)	
	1.0 Ltr	0.25 Ltr
	5 Ltr Combo Pack (A+B)	
	4.0 Ltr	1 Ltr
<b>Consumption</b>	: approx. 100-200 g/m <sup>2</sup> (depending on the porosity of stone)	



EPOXY TECHNOLOGY<sup>®</sup>  
**Oxi2010**  
VURA

**VURA Oxi 2010** is a two-component, low viscous, transparent and non-yellowing epoxy resin system with a modified hardener. It is used for firmly closing cracks and pores of any type of natural stones even for light color stones.

#### CHARACTERISTICS

- Hardens relatively quickly
- It has highly penetrative properties on account of its low viscosity
- Clear transparent, best suitable for light natural stones
- Solvent free epoxy system
- Weather-resistant, Chemical resistant
- Excellent grinding and polishing properties
- Increases the firmness and improves the quality of natural stone surfaces
- Increases the yield and the productivity
- Excellent product to fill pinholes and cracks of light-colored marble
- Good reactivity at low temperature, medium hardness

#### USAGE / APPLICATION AREA

- All type of marble/granite
- Natural Stones

**VURA Oxi 2010** is mainly used in the stone-working industry for strengthening porous and fissured natural stone slabs, concrete and concrete ashlar and improving their surface qualities. In combination with spun glass fabrics, it is also used for strengthening brittle natural stone slabs.



	Part A	Part B
Color	: Transparent	Transparent
Mixing ratio (by weight)	: 2	: 1
Pot Life	: 35-40 minutes (20°C)	
Packaging	: 1.5 Ltr Combo Pack (A+B) 1.0 Ltr	0.5 Ltr
Consumption	: approx. 150-200 g/m <sup>2</sup> (depending on the porosity of stone)	



# COLORING SYSTEM<sup>®</sup> UniColor<sup>®</sup> Tint<sup>®</sup> VURA

Vura UniColor Tint is a coloring liquid pigment/tint in different color shades.

## CHARACTERISTICS








- Color matching of the adhesive to many common stone colours
- UniColor Tint can be used with different adhesives based on Epoxy, Polyester and PUR.
- High intensity pigment tint, easy adjustment of color shades
- Fluid consistency (of tint) makes it easier to mix with different consistency adhesives
- No fading – UV& light resistant tint
- Properties of the coloured adhesives would remain same

## APPLICATION AREAS

**Vura UniColor Tint** is used for coloring Oxi 7010, PoliFill-G, PoliMast-G and Vura Klear, also can be used for coloring Oxi 2010, Oxi 4010 and PoliFill-L. Thus, adhesive color can be matched as per stone color by adjusting the dosage of UniColor tint.



**Packaging :** 50 ml

							
<b>Color</b>	: Red	White	Black	Yellow Ochre	Beige	Grey	Green



## DENSIFICATION SYSTEM





# DENSIFIER<sup>®</sup> DenStone 200<sup>®</sup> VURA



**Vura DenStone 200** is a lithium chemistry based densifier and marble hardener that penetrates into the marble and reacts with the marble to form compounds which expand and fill the pores in the stone. Not only reduce the porosity but also leads to enhanced shine and longevity of polish.

Densification makes the marble harder and denser. It is colourless liquid increase the stone strength and provides high gloss finish. It is lithium chemistry for marble, natural stones, terrazzo and concrete.

## CHARACTERISTICS

- Easy application
- Strengthen the surface
- Penetrates and seals new and existing marble, natural stones, terrazzo and concrete
- Improves chemical and water resistance
- Prolongs finish of polished surfaces
- Resists stains and Increase abrasion
- Making surface easy to use and maintain
- Environmentally friendly, water based formula
- Interior and Exterior use
- Protects against efflorescence
- Enhance gloss after polish
- Preserves Natural look

## USAGE

For the treatment of ground and polished absorbent marble, natural stone, slate, limestone, sandstone, granite, travertine etc.

## COVERAGE

application after 200 grit, approx. 200-250 sq ft / litre, depending on the porosity of the stone.

<b>Color</b>	: Slightly cloudy
<b>Density</b>	: 1.02 g/ml
<b>Ph</b>	: 10.5-11.0
<b>VOC Content</b>	: <50g/ml
<b>Freeze Point</b>	: 0°C
<b>Packaging</b>	: 1 Ltr & 5 Ltr



DENSIFIER<sup>®</sup>  
**DenStone 800**  
VURA



**Vura DenStone 800** is a penetrating impregnating hardener with nano lithium treatment for natural stone, marble, terrazzo and polished concrete surfaces which has been ground and polished up to 800 grits. This reduces alkalinity (efflorescence), improves adhesion and reducing dusting. Used during the production (grinding and polishing) of marbles, natural stones, concrete or terrazzo surfaces. **Vura DenStone 800** is designed to enhance the process, making it easier to reprofile as well as reduce costly wear and damage to diamond abrasives

#### CHARACTERISTICS

- Penetrates and seals new and existing marble, natural stones, terrazzo and concrete
- Improves chemical and water resistance
- Deepens clarity and heightens gloss
- Increase abrasion resistance
- Reduces alkalinity / efflorescence
- Easy to use and maintain
- Interior and exterior use
- User friendly, non-whitening
- Environmentally friendly, water based formula
- VOC compliant

#### USAGE

For the treatment of polished absorbent marble and natural stone e.g. slate, marble, limestone, sandstone, granite, travertine etc.

#### COVERAGE

natural stone after 800 grit, approx. 250-280 sq ft/litre depending on the porosity of the stone

<b>Color</b>	: Slightly cloudy
<b>Density</b>	: 1.01 g/ml
<b>Ph</b>	: 10.5-11.0
<b>VOC Content</b>	: <50g/L
<b>Freeze Point</b>	: 0°C
<b>Packaging</b>	: 1 Ltr & 5 Ltr



DENSIFIER<sup>®</sup>  
**Robustner**  
VURA

**Vura Robustner** is a one component liquid product derived from ethyl esters of silicic acids. The product is converted into the natural binding agent silica gel and ethanol by the catalytic reaction with air humidity. Approx. 450-550 g of silicic acid gel is produced out of 1 kg Vura Robustner.

#### CHARACTERISTICS

- Ready-to-use one component product
- Easy application
- Weather-resistant and non-yellowing
- Fluid consistency - good penetration
- Very high contents of active substances
- No closing of the pores, the stone retains its ability to breathe
- Transparent-colorless, therefore suited for light colored natural stones
- Solventless

#### APPLICATION AREAS

**Vura Robustner** is used to solidify absorbent mineral natural stones (sandstone, tuff stone, limestone etc.) or cast stones (stucco or fresco). The colour of the stone is not intensified and the natural breathing properties of the stone are preserved.



<b>Color</b>	: Colorless
<b>Coverage</b>	: appr. 0.1-2.5 m <sup>2</sup> /litre
<b>Density</b>	: Approx. 1.0 g/cm <sup>3</sup>
<b>Content of Active Substance</b>	: 100%
<b>Packaging</b>	: 1 Ltr



# POST PROTECTION SYSTEM



HYDROPHOBIC<sup>®</sup>  
**SanStone**  
 VURA



**VURA SanStone** is a ready-to-use water-based impregnating sealer for natural stones. It is a high quality and economical water repellence system for mineral and alkaline substrates. It does not changes the appearance of the substrate & gives a long lasting protection.

#### CHARACTERISTICS

- Deep penetration
- Easy to use – Brushable / Sprayable
- UV resistance
- Durable
- Water repellent
- Retains breathability of substrate (does not trap moisture)
- Resistance to alkalis
- Tack-free drying
- Invisible coating, does not change the color
- Cost effective

#### WATER REPELLENT TREATMENT FOR

- Limestone & sandstones
- Clay, concrete & mortar
- Mangalore tiles
- Natural and artificial porous stones
- Bricks



<b>Color</b>	: Clear Transparent
<b>Form</b>	: Liquid
<b>Density</b>	: 1.03 g/ml
<b>Surface Dry Time</b>	: 2-4 hrs
<b>PH</b>	: 13 to 14
<b>Application</b>	: By Brush or Spray
<b>Coverage</b>	: On porous substrate: 70-200 Sq ft. / litre On low porous substrate: 200-300 Sq ft. / litre
<b>Packaging</b>	: 1 Ltr & 5 Ltr



# HYDROPHOBIC<sup>®</sup> AquaRepWR<sup>®</sup> VURA



VURA AquaRep WR is a ready-to-use water-based water repellent for natural stones. It is a high quality and economical water repellence system for mineral and alkaline substrates. It does not changes the appearance of the substrate & gives a long lasting protection.

## CHARACTERISTICS

- Easy to use – Brushable / Sprayable
- UV resistance
- Durable
- Water repellent
- Retains breathability of substrate (does not trap moisture)
- Resistance to alkalis
- Tack-free drying
- Invisible coating, does not change the color
- Cost effective

## WATER REPELLENT TREATMENT FOR

- Limestone & sandstones
- Clay, concrete & mortar
- Mangalore tiles
- Natural and artificial porous stones
- Bricks

<b>Color</b>	: Clear Transparent
<b>Form</b>	: Liquid
<b>Density</b>	: 1.02 g/ml
<b>Surface Dry Time</b>	: 3-4 hrs
<b>pH</b>	: 10-12
<b>Application</b>	: By Brush or Spray Water Repellency Bead form
<b>Coverage</b>	: 70 to 200 Sq ft. / litre (depending on the porosity of stone)
<b>Packaging</b>	: 20 Ltr



# HYDROPHOBIC & OLEOPHOBIC VURA<sup>®</sup> Prevento

**Vura Prevento** is a solvent based impregnator for façade, used for natural porous stones and preserves a natural look. It is hydrophobic and oleophobic stone impregnator. It is an economical nano impregnating sealer designed for protection of porous stones against water, oil and other stains.

## CHARACTERISTICS

- Nano Impregnating technology
- Hydrophobic and oleophobic based product
- Designed for protection of porous stones
- Preserves natural look
- Weather resistant
- Microbond protection

## USAGE

- Natural stones such as marble
- Sandstones
- Granite
- Travertine
- Limestone

<b>Color</b>	: Transparent
<b>Form</b>	: Liquid
<b>Density</b>	: 0.87 g/ml
<b>Expected wear</b>	: 3-5 yrs
<b>Packaging</b>	: 1 Ltr





# HYDROPHOBIC & OLEOPHOBIC PowerSeal Pro<sup>®</sup> VURA



**Vura PowerSeal Pro** is a fluoropolymer based ready to use product, which is weather resistant, UV resistant, premium nano impregnating sealer providing ultimate protection against water, oil and other stains. PowerSeal Pro is absorbed by the stone due to the capillary forces, however, without closing the pores, therefore the product is very effective and durable.

## CHARACTERISTICS

- Fluoropolymer based chemistry
- Nano impregnating technology
- Oleophobic and Hydrophobic
- Fast curing and development of protective effect
- Low colour enhancement
- Very good oil- and grease stain repellent effect
- Very good reduction of water- and dirt absorption when exposed to moisture and high humidity
- Fast liberation of humidity during dry periods due to high vapor permeability
- Surfaces able to breath because there is no surface layer
- Non yellowing
- Maximum protection against stains
- Resistance to UV radiation
- No release of methanol during cure/drying
- Preserve natural look

## USAGE

- Natural stones
- Travertine
- Marble
- Sandstone
- Granite
- Limestone

<b>Color</b>	: Clear Transparent
<b>Form</b>	: Liquid
<b>Density</b>	: 0.8 g/ml
<b>VOC Content</b>	: <800g/1L
<b>Working Temperature</b>	: 5 to 35°C
<b>Expected Wear</b>	: 5 years (depending on abrasion rate and texture of surface)
<b>Coverage</b>	: 100-250 sq ft./litre
<b>Packaging</b>	: 1 Ltr



HYDROPHOBIC & OLEOPHOBIC<sup>®</sup>  
**PowerSeal+**  
VURA



## TRANSPARENT SURFACE PROTECTION AGENT, EXCELLENT WATER & OIL REPELLENT AND STAIN RESISTANT TO THE TREATED SURFACE

**Vura PowerSeal +** is water based synthetic polymer , provides a transparent and durable surface treatment for various kind of building materials such as Polished Porcelain Tiles, Natural stones, Marble and Granite, Terracotta, concrete and bricks. It provides excellent water and oil repellency to the treated surfaces, as well as stain resistance against oil, coffee, Ketchup and mustard among the others. **Vura PowerSeal +** is ready to use product so no dilution is required.

**Vura PowerSeal +** does not create a film on the surface and does not affect the original color and breathability of the material. The surfaces treated with **Vura PowerSeal +** are easy to clean without altering original appearance of the stone.

### CHARACTERISTICS

- Water and oil-repellent with natural finish
- Excellent anti stain properties
- Easy to clean properties
- Long lasting treatment
- Water based
- Extreme Eco compatible
- The best environmentally-friendly stain protection for porcelain tiles, natural stone, marble and granite with polished, brushed and matt smoothed finishes
- Reduces absorption without affecting the material's natural look
- It protects and facilitates cleaning
- It is also ideal for grouting joints, ceramic and crackle effect surfaces, grit, resin- marble, and stone slabs
- Is also suitable for treating coloured cement tiles and manufactured stones
- It provides an anti-graffiti protection that prevents graffiti paint from bonding to surfaces. It speeds the cleaning process because graffiti can be easily removed.

**Color**

: Clear

**Storage Temperature**

: 5°C to 30°C

**Working Temperature**

: 10°C to 30°C

**Coverage**

: Approximate coverage (1 L litre)

(Coverage shown for guidance  
Purposes only and for single coat)

Polished Porcelain Tiles	30-50 m2
Polished Marble / Granite	20-30m2

**Packaging**

: 1 Ltr

The background is a close-up of a wood surface with a prominent grain pattern. Numerous water droplets of various sizes are scattered across the surface, reflecting light. A dark rectangular box with a white border is centered horizontally, containing the text "ENHANCER SYSTEM" in white, bold, sans-serif capital letters.

**ENHANCER SYSTEM**



# COLOR ENHANCER & HYDRO-REPELLENT

## EnHanso<sup>®</sup>

VURA



**Vura EnHanso** is a ready to use, solvent-based, special impregnation technology that intensifies the natural look of the stone and provides resistance to oil and stains. It is suitable for ageing all types of marbles, travertines, stones, granites and agglomerates to obtain a wet effect both for indoor and outdoor. The product does not change the colour when is exposed to the ray sun. It can be applied on rough, sanded, brushed, flamed or honed surfaces to obtain the wet effect.

### CHARACTERISTICS

- Enriches color
- Maintains the gloss of the polish
- Does not form a layer on the surface of the stone
- Allows the stone to breathe
- Excellent weather and UV resistance
- Durable
- Non-yellowing
- For interior and exterior use
- Long working time
- Imparts wet look
- Water, Oil and dirt resistant

### USAGE / APPLICATION AREAS

- Natural Stones such as Marbles, Granites, Travertine, Limestone, Sandstone
- Bricks
- Artificial / Agglomerate Stone

### COVERAGE

- approx. 10-20 m<sup>2</sup> / litre. The consumption is depending on the porosity of the material / stone.

<b>Color</b>	: Transparent/opalescent
<b>Density</b>	: 0.92 g/ml
<b>Application</b>	: microfiber cloth / mop or through Agro spray gun.
<b>Packaging</b>	: 250 ml & 1 Ltr

A close-up, low-angle shot of a highly polished marble floor. The marble has a light cream or off-white base color, with intricate, flowing veins of gold, tan, and dark grey. The surface is very reflective, showing clear reflections of the surrounding environment, including what appears to be a window or glass partition in the upper right. The lighting is bright and even, highlighting the natural texture and patterns of the stone.

**TILE / STONE CLEANER**



TILE / STONE CLEANER

**CoreClean®**  
VURA



## PURPOSE HEAVY DUTY TILE CLEANER

**Vura CoreClean** is powerful, fast acting, heavy duty Hydrochloric based cleaner for regular cleaning of dirt and stains on tile surfaces, designed for daily maintenance of tiles. It may also be used as general purpose cleaner on other acid resistant surface. It is designed for removal of cement residues, efflorescence and most oxide stains.

### CHARACTERISTICS

- Ready to Use
- Fast acting
- Easy to apply and use
- Removes cement film
- Removes, residues, efflorescence and most oxide stains
- For interior & exterior cleaning applications of Tiles surfaces floor and wall

### SCOPE OF USE

- All Unglazed Ceramic Tile
- Glazed ceramic Tile
- Glass Tile
- Vitrified Tile
- Glass Mosaic Tile
- Porcelain Tile
- Quarry (Pre-wet surface prior to application to reduce absorption)
- Terracotta (Pre-wet surface prior to application to reduce absorption)
- Stone (Pre-wet surface prior to application to reduce absorption)

**For Stone Cleaning:** (Recommended dilution with water - 1:10-1:15)

(Note: not all stones can handle acid cleaning, so always check the stone type before using any acid-based cleaner)

**Color** : Light Yellow

**Packaging** : 1 Ltr & 5 Ltr

**Appearance** : Liquid


**Coverage** : Coverage depends on the porosity of surface and intensity of stains on the surface.

# OUR GREEN PROMISE



**ONE UNIT = ONE TREE**

To design a sustainable world is a fundamental commitment for us. We have adopted this giving back to the planet module of sales, where we plant one tree for every unit of Vura product we sell. With this initiative, we focus on planting trees in environmentally and economically challenged areas.



## Vura Bau-Chemie LLP

### **REGD. OFFICE:**

13th Floor, Elite Business Hub, Sola, Ahmedabad 380060, Gujarat, India.  
**079 4849 2890 | [hello@vura.ae](mailto:hello@vura.ae) | [Vura.ae](http://Vura.ae)**

### **MANUFACTURING FACILITY 1:**

At Post - Badpura Village, Gandhinagar Vijapur Highway, Ta. Mansa,  
Dist. Gandhinagar 382835, Gujarat, India.

### **MANUFACTURING FACILITY 2:**

Block/Survey No. 1455, Old Survey No. 901/1, Ranasan, Vijapur,  
Mahesana 384570, Gujarat, India.

### **MANUFACTURING FACILITY 3:**

B-34, Near Aravali Toyota, M.I.A., Alwar 301030, Rajasthan, India.

### **WAREHOUSE FACILITY 1:**

H.No. 492/1 At Shah Commercial Complex, Village Dapode, Bhiwandi,  
Dist. Thane 421302, Maharashtra, India.

### **WAREHOUSE FACILITY 2:**

C/O EFC Logistics India Pvt. Ltd., NH-6, Near Kona More, Village  
Pakuria, Post Office - Lakshmanpur, Howrah 711014, West Bengal, India.

### **WAREHOUSE FACILITY 3:**

SF.No. 196/3C6, Pulla Gounder Thottam, Irugur,  
Coimbatore 641103, Tamilnadu, India.

### **WAREHOUSE FACILITY 4:**

76-18-56, Iron Yard Bhavanipuram, Bhavanipuram,  
Vijayawada, NTR, Andhra Pradesh 520012, India.